

# YUKON ULTIMATE CNG SAE 15W-40

PRODUCT DATA SHEET



# Product description

Yukon Ultimate CNG is formulated to provide exceptional control of deposits, wear, and oil oxidation and oil nitration in the high- output mobile, compressed natural gas (CNG) fueled engines. Yukon Ultimate CNG meet mobile engine performance requirements for Cummins B& C series engines as well as Detroit Series 50 and Series 60 engines. Yukon Ultimate CNG is suitable for mono fuel application or Dedicated NGV.

#### Features and Benefits

- Superior anti- oxidation, anti nitration, detergency
- Anti-wear protection
- Premium low ash
- Superior Long operational life
- Promotes maximum engine performance
- Superior viscosity retention

## Specifications & Approvals

- CUMMINS B&C Series engines
- Detroit Diesel Series 50 and Series 60

## **Typical Properties**

ITEM	UNIT	METHOD	15W-40
AAPEARANCE	-	-	В&С
VISCOSITY 40 °C	cSt	ASTM D445	108.7
VISCOSITY 100 °C	cSt	ASTM D445	14.52
VISCOSITY INDEX	-	ASTM D2270	137
COLOR	-	ASTM D1500	L5.5
CCS@ -20 °C	cPs	ASTM D5293	6780
TBN	mgKOH/g	ASTM D2896	5.11

\*More specified products information are available upon request