



Product Description

Yukon Gear Oil EP is highly refined mineral oils enhanced with sulphur extreme pressure additive technology outstanding thermal stability and high load carrying capacity. Yukon Gear Oil EP recommended for the lubrication of industrial gear boxes using forced circulation or splash and oil bath lubrication. It may be used for the lubrication of spur and helical gears and in some lightly loaded worm type gear application. . The additives are compatible with the ferrous and non-ferrous metals used in industrial gear units.

Feathers & Benefits

- Clean gear additive technology ensures low deposit formulation enhanced filter life.
- Full extreme pressure (EP) performance gives maximum protection of gears against wear and shock -loading.
- High protection against corrosion and wear resulting in less maintenance.

Performance

- U.S. Steel 224, AGMA 9005.D94
- Cinicinnati Milacron Approvals
- DIN 51 517, Part 3

Typical Properties

Properties	UNIT	METHOD	ISO 68	ISO 150	ISO 220	ISO 320	ISO 460	ISO 680
Appearance	-	Visual	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
Color	-	ASTM D1500	L1.5	L2.0	L2.0	L2.0	L2.0	L2.0
Viscosity @ 40°C	cSt	ASTM D445	65.29	156.5	232.0	332.5	479.7	695.9
Viscosity @ 100°C	cSt	ASTM D445	9.139	15.01	19.73	25.04	31.86	42.72
Viscosity Index	-	ASTM D2270	117	95	95	97	97	103

*More specified products information are available upon request