



Product Description

Yukon Ultimate S3 X is premium quality engine oils, has been developed to be a high speed, heavy duty and continuous driving .With excellent engine protection and cleaning power. Yukon Ultimate S3 X offers improved added for fleet customers through oil- drain intervals, resulting oil and fuel economy and cost saving maintenance.

Yukon Ultimate S3 X is recommended for use in gasoline and diesel engine operating in moderate and severe service applications. This include engines on high- way, off –road, turbo diesel engine, construction farm woodlands, marine and stationary power plants. Yukon Ultimate S3 X is manufactured from high quality base stocks and selected additives.

Feathers & Benefits

- Trusted protection for any car
- Highly dependable, year-round protection
- Long operational life
- Excellent engine cleanliness and low combustion residues
- Promotes maximum engine performance
- Superior viscosity retention

Performances

- API CI-4, CH-4, CG-4, CF-4, CF, SL
- ACEA E3-96 # 4 / E5-02
- ACEA A3-02 / B3-98 # 2 / B4-02
- GLOBAL DHD-1
- MB p228.3 (PA), MAN 3275 (PA)
- VOLVO VDS-2, 3
- CUMMINS 20071/6/8, 20072/7
- MACK EO-M, EO-M PLUS
- JASO DH-1 (QUALITY)



Typical Properties

<i>Properties</i>	<i>UNIT</i>	<i>METHOD</i>	<i>15W-40</i>	<i>20W-50</i>
APPEARANCE	-	VISUAL	Bright & Clear	Bright & Clear
VISCOSITY 40 °C	cSt	ASTM D445	114.5	167.8
VISCOSITY 100 °C	cSt	ASTM D445	15.26	18.68
VISCOSITY INDEX	-	ASTM D2270	139	125
COLOR	-	ASTM D1500	L 2.5	L 2.5
TOTAL BASE NUMBER	mgKOH/g	ASTM D2896	9.20	9.20
CCS @ -25, -20, -15 °C	cPs	ASTM D5293	6,510	9,410

**More specified products information are available upon request*