



Product Description

Yukon Ultimate S4 blend with premium, highly refined base oils and high effective additives, it is an extra high performance diesel engine oil that provides excellent lubrication of diesel engine promoting extended engine life. This extra high performance provides outstanding performance in both modern, demanding low- emission diesel engines and older diesel engines operating on low or high sulphur fuel.

Yukon Ultimate S4 combines a blend of high performance base stocks with a progressive additive system to provide superior control of oil thickening due to soot build-up and high temperature as well as outstanding resistance to oxidation, corrosion, and high temperature deposits.

Feathers & Benefits

- High Thermal and oxidation stability – Reduced sludge build-up, deposits and viscosity increase
- Long operational life
- Advanced detergency / dispersancy - Excellent engine cleanliness and low combustion residues
- Promotes maximum engine performance

Performance

- API CI-4, CH-4, CG-4, CF-4, CF, SL
- ACEA E3-96 # 4 / E5-02
- ACEA A3-02 / B3-98 # 2 / B4-02
- GLOBAL DHD-1
- MB p228.3 (PA), MAN 3275 (PA)
- VOLVO VDS-2, 3
- CUMMINS 20071/6/8, 20072/7
- MACK EO-M, EO-M PLUS
- JASO DH-1 (QUALITY)



Typical Properties

<i>ITEM</i>	<i>UNIT</i>	<i>METHOD</i>	<i>15W-40</i>	<i>20W-50</i>
APPEARANCE	-	Visaul	Bright&Clear	Bright&Clear
VISCOSITY 40 °C	cSt	ASTM D445	110.8	160.0
VISCOSITY 100 °C	cSt	ASTM D445	14.81	18.02
VISCOSITY INDEX	-	ASTM D2270	138	126
TOTAL BASE NUMBER	mgKOH/g	ASTM 2896	9.20	9.20
CCS @-25 °C, -20, -15 °C	cPs	ASTM D5293	6340	8000

**More specified products information are available upon request*